



Email sales@smipumps.co.za Tel 011 397 5672

Address 13 Patrick Road Jetpark, Boksburg, Johannesburg

SMI -AIX Single Stage Suction Centrifugal Pumps



Application

Smi -Aix series pumps are often used in airconditioning, boiler water supply, cool water circulation, fire protection sprinkling system. It carry liquids which is similar to clean water in manufacturing process area. Allpumps is according to DIN24255 SPEC and is also available in Stainless steel.

Working Performance

Discharge diameter: DN32-300MM Capacity range: 4.5-1600m3/h

Head range: 5 - 150m

Speed: 1450rpm/min & 2900rpm (50Hz Electric

source)

Max speed: 3500 rpm(Electric source 60Hz

motors, Impeller size will decrease)

Working Pressure : 1.6Mpa Working Temprature : -10C - 85C

Shaft Seal

Use of Mechanical seal or Gland packing depends on customer application or choice

Type Description

EX: AIX100/40

AIX: AIX series single stage single suction

centrifugal pump

Seal Ring

Shaft sleeve

100: Discharge Diameter (mm)

40: Impeller diameters

Impeller sizes can be Machined to customer


requirements and needs


Part name	materials
Casing	HT250
Casing Cover	QT450-12, SS304, SS316
Impeller	HT250
Impeller	Bronze C95200, SS304, SS316
Shaft	2Cr13 ,SS431

SS304


Bronze C95200, SS304, SS316

Quick Selection Chart





Outline Dimensions SUCTION S



32-13 32-20 32-2	PUMP SIZE	SHAFT MODULE	SUCT.	DISCH.		Pl	JMP					SPACER	SHAFT	END	Weight (kg)						
132 160 100	SIZE	MODULE			Α	F	H1	H2	M1	M2	N1	N2	S1	В	W	N3	S2	Х	D	L	ِ ﴿ اِ
32-6 32	32-13		50	32			112	140			190	140			267	Ш					30
32.26	32-16						132	160	100	70	240	190		50							39
100 100	32-20						160	180			240	100									43
40-13 40-16 40-16 40-20 40-26 40-26 40-26 40-26 40-27 40-28 40-32H 35 50-13 50-13 50-13 50-26 50-26 50-32H 35 50-32H 35 50-32H 35 50-26 50-32H 35	32-26						180	225	125	95	320	250		65		110			Φ24		62
40-26 40-32H 35	40-13	25		40	80	300		140	1	70		160		50							
40-32H 35									100			_									_
40-32H 35			65		100			180				_									-
100 100							_	225	125	95		_		65							
Su-16 Su-1		35			125	470				ļ		_			342				Ф32	80	
S0-20							132	_		l	240	190	Ψ14			100					_
100 100		25			100	360	160	-	100	70	265	212		50	267			100	Φ24	50	-
Solid Soli		-	65	50				_		<u> </u>						110					
Section Sect												_		65		110					
65-16 25 80 80 65 80 65 80 65 80 80 65 80 80 80 65 80 80 80 80 80 80 80 8		35			125	470	225	_	405	٠.	345	280			342			140	Ф32	80	
65-20		ا م			100	١,,,	160		125	95	280	212		50		100	Ф14	100	Ф24	Н	-
65-28 35 35 35 40 80 40 45 80-36 35 100 80 80 45 125 125 125 125 125 125 125 125 125 12		25				360		_							267						_
65-32H 35			80	65						_		_		65							
80-16		35				470		_	160	120		_	Ф18	80	342			140	Ф32		-
80-20		05				<u> </u>				<u> </u>								400	404		_
80-26		25		80	125	470 519			125	Н		_	Ф14		267			100	Ф32	80	
80-32H 100 125 250 315 360 180 225 250 315 360 180 225 250 315 360 315 315 360 315			100					_			345	280		65	342						-
80-32H 100-16 25 100 26 35 125 100 27 280 315 100 20 100-26 35 125 100 25 315 100 25 32 125 36 315 160 120 400 315 400		35	100						160		400	315	Ф18	80	042						
100-16			-						100		440	055			222						_
100-20 100-20 35 125 100		-						-	405	0.5			211			110				_	_
100-26		25				360		225	125	95		_		50	342			100	Ψ24	50	
100-26		25	125	100		470		280	160		400	315									_
100-40		35						245			440	355	Ф18	80							=
125-26 35 150 125		45						-	200		500	400	222	400							
125-26 35 35 150 125		45			140	330		200	150	500	400	υ φ23	100	370					-		
125-32		35		125		470	250	315	160	120	400	315	Ф18	80	370 367 370			140	Ф32	80	
125-40			150				280	355						100						\vdash	
150-20 35G		45				530					500	400	Ф23						Ф42	110	_
150-26		35G				495		400			550	450	Φ20						Ф32	80	
150-32		336		0 150		-33		255				_	Ψ20							80	_
150 - 40 150 - 40 150 - 40 150 - 40 150 - 40 150 - 40 150 - 50 150 - 40 150 - 50		45	200		160	530		-			450	_									_
150-50 60 180 670 375 500 55		"				530			200		550	450									
200-26		60			180	670				150	660	550							Ф55	110	_
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$					_	_					-	1 330	ΨΖ3	1-40							
200-40 55 250 200 670 355 350 200 670 355 350 300 240 720 600 400 500 300 240 720 600 400 500 300 240 720 600 400 500 500 400 400 500 40				200	200		200				330	450		100					Ψ4Z		-
200-50 70 210 760 400 500 300 240 720 600		55	250				355	450			550			'**	511			180	Ф48		
250-32 60 300 250 670 355 525 250 175 600 500 423 100 511 120 540 401 453 250-50 250 350 300-32 75 350 300 259 375 403 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 562 300 500 500 500 500 500 500 500 500 500		70				760	400	500	300	2/10	720	600	Ф27	160	520				Φ65	140	
250-40 70 300 250 780 400 500 250 780 400 500 240 873 425 545 300-32 75 350 300 259 375 403 562 300 562 300 300 300 300 300 300 300 300 300 30			300	00 250	200	-		-		_	_	550									
250-50 240 873 425 545 300-32 75 350 300 259 975 403 562 200 750 600 427 140 634 423 465		-							230	_	_	500			F40						
300-32 75 350 300 259 975 403 562 200 750 600 Ф27 140 634 Ф23 Ф70 147 520		10				_	_	_	000			\vdash			_	140		1	Ψ65	140	
350-32 75 350 300 255 975 405 302 200 750 427 140 654 425		75		350 300		0/3			300	-	_	600	Ф27		_		Ф23		Ф70	147	_
	300-32	'	350		280	875	500	600			800	660		150	626						583

Pump Structures

