

	PUMP SIZE	FRAME	KW RATING		For contact details - visit www.smipumps.co.za			PUMP PERFORMANCE CURVE REFERENCE WPG 100MP30 Printed May 2008			
	100	DAM	60								
		DDAM	110								
		E*	120								
	TYPE	EE	225		E4147				CASING		
	MP	IMPELLER		VANES					TYPE	MAT'L	VANE Ø
5		CLOSED		METAL				365		METAL	
COPYRIGHT © SMI PUMPS (PTY) LTD T/A SMI PUMPS					GLAND SEAL PUMP					MIN PASSAGE SIZE 51 mm SPHERE	
WE RESERVE THE RIGHT TO MODIFY OR DELETE IMPELLERS WITHOUT PRIOR NOTICE					POWER CONSUMED MAY INCREASE BY 5% WITH CENTRIFUGAL SEAL						
CURVE SHOWS APPROXIMATE PERFORMANCE FOR CLEAR WATER (IN ACCORDANCE WITH PUMP TESTING ISO9906-1999 GRADE 2 (ISO2548 CLASS C)). FOR MEDIA OTHER THAN WATER, CORRECTIONS MUST BE MADE FOR DENSITY, VISCOSITY AND/OR THE PRESENCE AND EFFECTS OF SOLIDS					NORM MAX RPM 1830						
* Indicates standard frame size fitted, refer to Head Office for availability of frame sizes quoted, other than standard. Operating pumps over maximum speed refer to Head Office. Rated kilowatts is the maximum that any particular bearing assembly can transmit and is not the maximum motor frame size that can be fitted to any particular bearing assembly.											

