

	PUMP	FRAME	KW RATING		For contact details - visit www.smipumps.co.za		PUMP PERFORMANCE CURVE REFERENCE WPG 50MP30 Printed May 2008
	SIZE	C*	30				
	50	CC	55				
	TYPE						
	MP	IMPELLER		C2147		CASING	
	VANES	TYPE	MAT'L	VANE Ø	MAT'L		
	5	CLOSED	METAL	214	METAL		
COPYRIGHT © SMI PUMPS (PTY) LTD T/A SMI PUMPS			GLAND SEAL PUMP				MIN PASSAGE SIZE 25 mm SPHERE
WE RESERVE THE RIGHT TO MODIFY OR DELETE IMPELLERS WITHOUT PRIOR NOTICE			POWER CONSUMED MAY INCREASE BY 5% WITH CENTRIFUGAL SEAL				
CURVE SHOWS APPROXIMATE PERFORMANCE FOR CLEAR WATER (IN ACCORDANCE WITH PUMP TESTING ISO9906-1999 GRADE 2 (ISO2548 CLASS C)). FOR MEDIA OTHER THAN WATER, CORRECTIONS MUST BE MADE FOR DENSITY, VISCOSITY AND/OR THE PRESENCE AND EFFECTS OF SOLIDS				NORM MAX RPM 3170			
* Indicates standard frame size fitted, refer to Head Office for availability of frame sizes quoted, other than standard. Operating pumps over maximum speed refer to Head Office. Rated kilowatts is the maximum that any particular bearing assembly can transmit and is not the maximum motor frame size that can be fitted to any particular bearing assembly.							

