

	PUMP	FRAME	KW RATING	For contact details - visit www.smipumps.co.za				PUMP PERFORMANCE CURVE REFERENCE
	SIZE	CAM	30					
	75	CCAM	55					
		D*	60					
	TYPE	DD	110					
MP	IMPELLER				D3147	CASING	WPG 75MP30	
	VANES	TYPE	MAT'L	VANE Ø	MAT'L	Printed May 2008		
	5	CLOSED	METAL	245	METAL			
COPYRIGHT © SMI PUMPS (PTY) LTD T/A SMI PUMPS			GLAND SEAL PUMP					MIN PASSAGE SIZE 36 mm SPHERE
WE RESERVE THE RIGHT TO MODIFY OR DELETE IMPELLERS WITHOUT PRIOR NOTICE			POWER CONSUMPTION MAY INCREASE BY 5% WITH CENTRIFUGAL SEAL					
CURVE SHOWS APPROXIMATE PERFORMANCE FOR CLEAR WATER (IN ACCORDANCE WITH PUMP TESTING ISO9906-1999 GRADE 2 (ISO2548 CLASS C)). FOR MEDIA OTHER THAN WATER, CORRECTIONS MUST BE MADE FOR DENSITY, VISCOSITY AND/OR THE PRESENCE AND EFFECTS OF SOLIDS				NORM MAX RPM 2750				
* Indicates standard frame size fitted, refer to Head Office for availability of frame sizes quoted, other than standard. Operating pumps over maximum speed refer to Head Office. Rated kilowatts is the maximum that any particular bearing assembly can transmit and is not the maximum motor frame size that can be fitted to any particular bearing assembly.								

